AMENDMENT UNDER 37 C.F.R. § 1.111 Attorney Docket No.: Q77488

Application No.: 10/662,440

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the

application:

LISTING OF CLAIMS:

1. (currently amended): A pressure-sensitive adhesive tape comprising a supporting

substrate and a pressure-sensitive adhesive layer formed on at least one side of the supporting

substrate, the supporting substrate having an uneven portion on one side , wherein a maximum $% \left(1\right) =\left(1\right) \left(1\right) \left($

stress at an elongation of not more than 50 % of the pressure-sensitive adhesive tape is larger

than the stress at break, wherein the elongation at break of the pressure-sensitive adhesive tape is

from 100 to 300 %, wherein the substrate is formed from a resin composition comprising : high-

density polyethylene and low-density polyethylene, said low-density polyethylene having a

density equal to or less than 0.919 g/cm³, wherein said high-density polyethylene and said low-

density polyethylene are present in a weight percent ratio selected from the range of 10/90 to

90/10, and a filler in an amount of not more than 5 parts by weight based on 100 parts by weight

of the resin composition.

2. (previously presented): The pressure-sensitive adhesive tape according to claim

1, wherein the maximum stress at an elongation equal to or less than 50 % is at least 11 N/10

mm.

3. (canceled).

2

AMENDMENT UNDER 37 C.F.R. § 1.111 Attorney Docket No.: Q77488

Application No.: 10/662,440

(canceled).

 (original): The pressure-sensitive adhesive tape according to claim 1, wherein the supporting substrate is transparent.

6. (previously presented): The pressure-sensitive adhesive tape according to claim

1, wherein the density of the low-density polyethylene is from 0.880 g/cm3 to 0.919 g/cm3.

7. (previously presented): The pressure-sensitive adhesive tape according to claim

1, wherein the density of the low-density polyethylene is from 0.910 g/cm3 to 0.919 g/cm3.

8. (previously presented): The pressure-sensitive adhesive tape according to claim

1, wherein the density of the high-density polyethylene is from 0.940 g/cm³ to 0.970 g/cm³.

9. (previously presented): The pressure-sensitive adhesive tape according to claim

1, wherein the density of the high-density polyethylene is from 0.950 g/cm³ to 0.965 g/cm³.

3